



# Optiprimer Basestain TR

Contains no or minimal solvents  
Waterborne flowcoat quality for industrial use

## PRODUCT DESCRIPTION

DRYWOOD Optiprimer Basestain TR is a transparent waterborne industrial wood impregnation primer (flowcoat quality) for interior and exterior wooden joinery and other wood constructions.

See [www.drywood.nl](http://www.drywood.nl) for use of this product in a total paint system.

## TECHNICAL DATA

General

DRYWOOD Optiprimer Basestain TR is based on a combination of waterborne binders and is suited as a transparent waterborne industrial wood impregnation primer. It can be applied by flowcoating, dipping, spraying or brushing. It is designed to be used in a total paint system with DRYWOOD Optifinish TR.

Properties

Drywood Optiprimer Basestain TR has good impregnation into and coloration of the wood and excellent filling, flow and levelling properties. The product has good adhesion, dries very quickly and has good sandability.

Colours and packaging

DRYWOOD Optiprimer Basestain TR is available in almost all transparent colours. The product is available in 60, 200 and 1000 liter containers. Shelf-life is at least 6 months in unopened and closed packaging and at frost-free storage. Keep packaging closed airtight after opening.

Density

1.01 - 1.05 g/L

Solids content

approx. 16 Vol%

VOC content

max. 50 g/l EU-Limit (2004/42/EG annex. II A(d): 130 g/l)

Consumption

appr. 10 m<sup>2</sup>/l at 100 g/m<sup>2</sup>

## APPLICATION

General

DRYWOOD Optiprimer Basestain TR can be applied by dipping, flowcoating, spraying or brushing on a clean surface, sanded and dry, free of dust and grease. Application viscosity is 12-15 s DIN4. Drying time depends on layer thickness, temperature, relative humidity and ventilation. The product should be used above 8°C with maximum 70 % relative humidity.

Drying times at 15 °C and 60 % R.H. at 100 g/m<sup>2</sup>: dust-free after 30 min., touch-dry after approx. 1 hour and repaintable after approx. 2 hours.

Stir well immediately prior to use. Use the pure product.

Environment

The product has little smell and is not flammable. Due to the preservatives it has some toxicity to the environment.

Cleaning

Clean equipment after use with water and soap or other suited cleaners.

Waste

Material and all related packaging must be disposed in a safe way in accordance with full requirements of local authorities.

## SAFETY INFORMATION

see Material Safety Data Sheet

This product contains propiconazole. May produce an allergic reaction

PDS no. 074001EN  
Revision 21 april 2011

The above information is given according to our present knowledge. DRYWOOD COATINGS B.V. tries to keep the technical information up-to-date. In case further dates or informations of importance should come to our disposal this technical information-sheet will be updated (see date of issue). We reserve the right to modify paint-formula-tions, processing-instructions, etc. without previous notice. We can not accept liability for mis use of the product or any loss or damage arising out of such.

