

BD Topcoat TR SG

Contains no or minimal solvents
 Waterborne spray quality for industrial use

PRODUCT DESCRIPTION

DRYWOOD BD Topcoat TR SG is a transparent waterborne silk matt industrial finish (spray quality) for interior wood such as interior joinery, furniture, plywood, MDF and other interior wood applications.

See www.drywood.nl for use of this product in a total paint system.

TECHNICAL DATA

General	DRYWOOD BD Topcoat TR SG is based on waterborne binders and can be used as a transparent silk matt finish (spray quality) for interior products.	
Properties	DRYWOOD BD Topcoat TR SG is a very quick drying product, has a good dry adhesion on various - such as BD Coat TR G40 pretreated - wooden substrates. The product has nice levelling properties, has a very good clarity and scratch resistance, has a good to very good chemical resistance and has excellent blocking properties. The product has been tested according to Dutch standard BRL 2211 (tests performed after 14 days drying at min. 15 °C).	
Colours and packaging	DRYWOOD BD Topcoat TR SG is available in almost all transparent colours. The product is available in 20, 60, 200, 600 and 1000 liter containers. Shelf-life is at least 6 months in unopened and closed packaging and at frost-free storage. Keep packaging closed airtight after opening.	
Density	1.04 - 1.10 kg/l	(depending the colour)
Solids content	approx. 35 Vol%	(depending the colour)
VOC content	max. 45 g/l	EU-Limit (2004/42/EC annex. II A(d): 130 g/l)
Consumption	appr. 9 m ² /l	at 35 µm dry film thickness

APPLICATION

General	<p>DRYWOOD BD Topcoat TR SG can be applied by airless or airmix spraying or with air assisted or HVLP spraying on a clean surface, sanded and dry, free of dust and grease at a temperature of at least 8 °C. Bare wood must be primed with BD Coat TR. Drying time depends on layerthickness, temperature, relative humidity and ventilation. Typical layerthickness is 100-120 g/m².</p> <p>Drying at min. 15 °C and max. 60 % R.H.</p> <p>Stirr well immediately prior to use and check colour.</p>
Environment	The product has low toxicity to environment, has little smell and is not flammable.
Cleaning	Clean equipment after use with water and soap or other suited cleaners. Dilute with water.
Waste	Material and all related packaging must be disposed in a safe way in accordance with full requirements of local authorities.

SAFETY INFORMATION

see Material Safety Data Sheet

PIB nr. 086201EN
 Revisiedatum 13 juli 2011

The above information is given according to our present knowledge. DRYWOOD COATINGS B.V. tries to keep the technical information up-to-date. In case further dates or informations of importance should come to our disposal this technical informations-heet will be updated (see date of issue). We reserve the right to modify paint-formulations, processing-instructions, etc. without previous notice. We can not accept liability for mis use of the product or any loss or damage arising out of such.